

## EasyJoint SG

EasyJoint SG is a performance silicone grease jointing lubricant with high temperature stability for water, soil and waste drainage and gas pipes.

This unique blend acts as a dual-purpose lubricant and sealant on gas valves creating an airtight seal.

### CONTAINS:

Silicone Grease

## Product Information

- Used in all uPVC push-fit systems and other pipework including gas pipes to lubricate 'O' rings, seals and joints during assembly
- Acts as dual-purpose lubricant and sealant on gas valves
- Creates a waterproof and airtight joint seal
- Compatible with all common 'O' ring and seal materials (EPDM, NBR, SBR, NR, CR) with no 'seal swell'
- WRAS approved\* approved for use in contact with potable (drinking) water
- Suitable for hot and cold-water applications up to 85°C
- Stable in daylight and UV light between -50°C and +280°C
- Odourless and non-toxic
- Conforms to BS 6920 "Items which have passed full tests of effect on water quality".

## TECHNICAL DATASHEET

### sizes available

500g



### specification

Appearance:	Clear viscous liquid
Odour:	No odour
Specific Gravity @20°C:	0.97 – 1.01
Flash Point:	>200
Solubility:	Miscible in water

## Directions for Use

Ensure ring seal, socket and pipe end are clean and free from dirt.

Check that the seal is correctly located in the seal housing of the socket.

Apply a thin film of lubricant evenly to pipe end (especially the chamfer), gasket and inside the socket.

Push pipe end into socket to required depth.

**Storage:** Keep in original packaging. Store in a cool dry well-ventilated area out of direct sunlight.