

EasyJoint SE

EasyJoint SE is a high performance stabilised silicone emulsion lubricant for easy and speedy assembly of plastic water pipes.

CONTAINS:

Silicone Oil

Product Information

- Used in all uPVC push-fit systems and other pipework to lubricate 'O' rings, seals and joints during assembly
- Compatible with all common 'O' ring and seal materials (EPDM, NBR, SBR, NR, CR) with no 'seal swell'
- WRAS approved* for use in contact with drinking water
- Suitable for hot and cold water applications up to 85°C
- Stable in daylight and UV light between -50°C and +280°C
- Water repellent, inert and non-toxic
- Conforms to BS 6920 "Items which have passed full tests of effect on water quality".

TECHNICAL DATASHEET

sizes available

100g



specification

Appearance:	White viscous liquid
Odour:	No odour
pH:	7.5 – 8.5
Specific Gravity @20°C:	0.98 – 1.02
Viscosity:	7000cPs approx
Flash Point:	>200

Directions for Use

Apply lubricant as recommended by the pipe manufacturer or as follows:

Ensure the spigot and joint are free from foreign matter.

Apply the lubricant using a brush or sponge around the entire circumference of the spigot and to the desired depth.

Storage: Store in original containers out of direct sunlight with the lids securely closed.