

EasyJoint SL

EasyJoint SL is a new generation silicone spray lubricant incorporating advanced spray technology for jointing water, soil and waste drainage and gas pipes.

This unique compressed technology provides the same spray pattern as a conventional 400ml aerosol and less flammable so can be stored safely.

Product Information

- Used in all uPVC push-fit systems and other pipework including gas pipes to lubricate 'O' rings, seals and joints during assembly
- Creates a waterproof and airtight joint seal
- Compatible with all common seal materials (EPDM, NBR, SBR, NR, CR) with no 'seal swell'
- WRAS approved* approved as safe for use in contact with drinking water
- Handy for use with guttering and downspouts
- 40ml pack delivery equivalent to a traditional 400ml aerosol
- Dramatically reduces distribution and warehousing costs and hazards
- Non-toxic, environmentally friendly

TECHNICAL DATASHEET

sizes available

40ml



specification

Appearance:	Clear viscous grease
Odour:	No odour
Specific Gravity @20°C:	0.96 – 0.98
Flash Point:	>200

Directions for Use

Use sparingly as this is a concentrated lube

Apply an even coat over all parts that require lubricating or to be assembled

Wipe away any excess with a dry cloth or paper towel

Storage: Keep in original packaging. Store in a cool dry well-ventilated area out of direct sunlight .