

EasyJoint LS

WRAS approved pipe jointing lubricant is a liquid form of vegetable-based technology which easily washes away once the pipe has been securely connected and fixed in position.

The liquid consistency ensures the suitability for jointing drinking water installations with hard to reach areas.

CONTAINS:

Surfactant and Lubricant

Product Information

- Typically used with plastic pipe material for drinking water installations.
- Compatible with all known seal materials such as EPDM, NBR, SBR, NR, CR with no 'seal swell'
- Spreads readily to get into hard to reach areas
- Easily washed away once pipe system assembly has been completed
- WRAS approved* approved as safe for use in contact with drinking water
- Safe, simple and easy application
- Conforms to BS 6920 "Items which have passed full tests of effect on water quality".

TECHNICAL DATASHEET

sizes available

250ml and 500ml



specification

Appearance: Pale straw liquid

Odour: Mild

pH: 6.5-7.5

Specific Gravity @20°C: 1.02

Directions for Use

Ensure ring seal, socket and pipe end are clean and free from dirt

Ensure the seal is correctly located in the seal housing of the socket

Mark the correct insertion depth on pipe end

Apply a thin film of lubricant evenly to pipe end (especially the chamfer), gasket and inside the socket

Push pipe end into socket until pipe insertion mark indicates the pipe has been jointed to the correct socket depth

Storage: Store in original packaging in a cool, dry and well-ventilated area out of direct sunlight.